



MORTAR RAKERS DSM



DSM MORTAR REMOVAL



DESCRIPTION : A 6mm thick blade. Good speed of cut and life.

USE ME FOR : All types of hard and abrasive mortar.

8MM SEGMENT HEIGHT

SEGMENTED KEY HOLE GULLETS

6MM BLADE WIDTH / STANDARD CORE

GOOD SPEED OF CUT & LIFE

SINTERED BOND



MATERIAL TYPE

MORTAR RAKING

HARD / DENSE MATERIAL

SOFT / ABRASIVE MATERIAL

MATERIAL TYPE	MORTAR RAKING
GLASS / REINFORCED PLASTIC	
POLYURETHANE	
FIBREGLASS	
MARBLE - DRY CUTTING	
STEEL BARS, PIPE & SECTIONS	
SG & GREY IRON	
PORCELAIN & HARD TILES	
CERAMIC TILES	
INDIAN STONE	
GRANITE	
SLATE	
CLASS A ENGINEERING BRICKS	
CLAY PAVIORS / PIPES / TILES	
FLINT AGGREGATE PRODUCT	
CLASS B ENGINEERING BRICKS	
HEAVILY REINFORCED CONCRETE	
MEDIUM REINFORCED CONCRETE	
LIGHTLY REINFORCED CONCRETE	
CONCRETE	
HARD YORK STONE	
QUARTZITE	
LONDON BRICK	
HARD CONCRETE PRODUCTS	
KERBS / LINTELS / BEAMS	
CAST PIPES	
BRICKS / CONCRETE FLAGS	
HAND MADE BRICKS	
FACING BRICKS	
CONCRETE ROOF TILES	
SOFT CONCRETE PAVIORS	
SAND BASED PAVIORS	
GREEN CONCRETE	
CEMENT SCREED	
LIGHTWEIGHT CONCRETE BLOCK	
HOT ROLLED ASPHALT	
ABRASIVE SAND / GRITSTONE	
ASPHALT OVER CONCRETE	
ASPHALT	
ABRASIVE MORTAR	

MORTAR RAKING

BASE

DIMENSIONS	DSM
(4 1/2") 115 x 22.2	115DSM ∞
(5") 125 x 22.2	125DSM ∞



THE ENTRY-LINE FROM DURO, WHERE PRICE AND PERFORMANCE ARE MATCHED TO OFFER GREAT VALUE OUTPUT THROUGHOUT THE RANGE.



HIGHLY SUITED
 NOT SUITABLE
 SUITABLE WITH RESERVATIONS

ORDER LINE: 01909 552470 / 1

WWW.DURO-DIAMONDS.COM

WWW.YOKOTA.CO.UK