

BUST SUPPRESSION



WITH BURO BUST SUPPRESSION

10L, 11L, 13L & GGL POLYETHYLENE

10L METAL

HAND PUMP & BATTERY POWERED



WITHOUT BURD BUST SUPPRESSION

WATER TANKS





10 LITRE TANK

T-161-MITAL #BURABILITY



Ideal for companies who would gain from its durability

FEATURES

- > 10 litre capacity
- > Highly durable 4m hose fully braided for flexibility
- > Bottom load hose
- > Metal pump mechanism
- > Durable metal body
- F > Wide robust base for stability
- > 6 bar pressure relief valve no leakage
- H > Pressure gauge
- > Wide funnel
- > Robust pump
- > Internal debris filter
- > Brass internal hose connector









60 LITRE TANK - BATTERY POWERED - FOR CONSTRUCTION SITES

DU-DST-69L-A

ECAPACITY



Ideal for construction sites, utility and highway sectors.

Battery powered - Metabo 18v

Up to 2 hours 50 mins run time*

Fully portable around site

Very robust unit

Programmable flow rates

- cutting / grinding
- watering
- core drilling
- cleaning

Auto shut off pump feature

Powerful pump

Brushless motor

Standard hose connections

Also suitable for cleaning equipment

BATTERY AND BATTERY CHARGER ARE INCLUDED BUT ALSO AVAILABLE SEPERATELY

Battery charge time up to 60 minutes

METABO 18V BATTERY	5840AC
METABO BATTERY CHARGER	5801AC

PROGRAMMABLE FLOW RATES

SPRAY MODE

MAX PRESSURE

BATTERY MAX RUNTIME

Cutting / Grinding Watering Core Drilling Cleaning

0.6 BAR (8.7PSI) 1.1 BAR (16 PSI) 1.5 BAR (21.7PSI) 1.7 BAR (24.6 PSI) Approx 2 Hrs 50 Min* Approx 2 Hrs 20 Min Approx 1 Hrs 45 Min Approx 1 Hrs 20 Min

Typical example of petrol saw use - 2 hours and 10 minutes of constant cutting / grinding usage before tank is empty of water Battery will last 2 hours and 50 minutes





13 LITRE TANK





The market leading tank for good reason - made from high density polyethylene

FEATURES

- A 13 litre capacity, strong polyethylene tank
 - > 5.6mm thick polyehtylene body ensures no deformation under pressure
- B Durable pump with efficient pressure build up:
 - > 60% less pumps required to reash HSE recommended flow rate - 20 pumps only
 - > Robust pump enabling constant use
 - > No pressure loss enabling constant flow
- C Quality hose clamps internal brass hose connection:
 - > Hose clamps & connectors enable high pressure retention
 - > Ensures no water loss
- D High quality water-stop & 4m hose length:
 - > Ensures no water loss
 - > Enables tank disconnection to allow refills
 - > 4m length increases tank manoeuvrability
- E 4 bar safety valve & high water flow rate:
 - > Guaranteed high pressure level ensures constant flow of water to cutting edge with no leakage
- High quality hose:
 - > Prevents hose kinking
- G Hose exit support spring:
 - > Prevents hose kinking
- H Stable & robust base:
 - > Wide base for increased tank stability
 - > Robust base material

FULL LIST OF ACCESORIES AND REPLACEMENT PARTS ON PAGES 43 & 44

> Pump kits / Internal hose kits External hose kits / Brass connectors Seal kits / Replacement valve kits Water stop connectors External hose connectors

Essential Selection Product





BP-BST-11L-STABIL

ESTABILITY



Made from high density polyethylene with a number of stability features ideal for the job site

FEATURES

- A > 11 litre capacity
- B > High density polyethylene body
- C > Wide base for stability
- D > Protective support ring
- E > Highly durable & flexible 4m hose
- F > 4 Bar pressure relief valve no leakage
- G > Wide funnel
- H > Robust pump
- > Internal debris filter
- J > Host exit support spring to prevent kinking
- K > Water resistant warning & advice label
- L > Extra strong external & internal brass hose connection

Essential Selection Product







STANDARD 10 LITRE TANK

D-DST-101





Ideal for contractors who require a more portable tank but want to retain its most important features

FEATURES

- A > 10L Capacity
- 3 > Wide funnel opening for easy filling
- C > 4 Bar pressure relief valve no leakage
- D > Reliable & robust pump mechanism
- > Water resistant warning & advice label
- F > Internal debris filter
- G > Highly durable 3m, fully flexible hose
- H > Extra strong internal brass hose connection
- I > Hose exit support spring to prevent kinking
- J > Sturdy & stable base
- K > Sturdy & comfortable handle

Essential Selection Product

BUST SUPPRESSION

TANK ACCESSORIES





REPLACEMENT PUMP KIT

Replacement pump for:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL
- > Sturdy & reliable handle > Robust pump mechanism
 - DP-DST-13L-PUMP-KIT



REPLACEMENT INTERNAL HOSE KIT

Replacement internal hose & debris filter for:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL

FEATURES

> Efficient internal water feed

DP-DST-13L-INT-HOSE



REPLACEMENT EXTERNAL HOSE

Replacement external hose for:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL



- > Highly durable
- > Kink free

DP-DST-13L-EXT-HOSE



REPLACEMENT VALVE KIT



Release of built up pressure during use of:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL



- > Valve operates using a traffic light system
- > Automatically releases when red section shows

DP-DST-13L-PRVAL-KIT

BUST SUPPRESSION

TANK ACCESSORIES





SEAL KIT

Set of replacement 'O' rings & seal for:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL

> Extends the life of each tank

DP-DST-13L-SEALS-KIT

PLUS

BRASS WATER STOP CONNECTOR



Higher performance water stop connector replacement for all DURO dust suppression tanks.

- > Extends the life of each tank > Solid brass manufacture
- > Standard hose lock fittings for all machine types

BRASS-CONNECTOR



WATER STOP CONNECTOR

Replacement water stop connector for all DURO dust suppression tanks.

> Standard hose lock fittings for all machine types

DP-DST-13L-WATERSTOP



EXTERNAL HOSE CONNECTOR



Replacement hose connector for use with:

- > D-DST-10L
- > DP-DST-13L
- > DP-DST-11L-STABIL

> Extends the life of each tank

DP-DST-13L-REPAIR